

DESCRIPTION

BIO FOR S is a wetting and foaming additive for forest fires, urban fires and industrial fires fighting.

Wetting effect 0.5 – 1% / Foaming effect 1 – 3%.

▲ **Wetting power** : the water with BIO FOR S deeply penetrates all solids, so multiplying the extinguishing power and preventing early fire restart. BIO FOR S increases the speed of extinction on vegetation fires, car fires, house fires, dumping site fires, plastic fires, tyre fires... The saving of water eases the cleaning of destroyed houses.

▲ **Foaming power** : BIO FOR S is usable at Low, Medium and High Expansion with all known equipment. Its foam clings and sticks to vertical structure for a long time.

▲ **Corrosion** : BIO FOR S contains an additive NITRATE-FREE with a strong inhibition effect against metal corrosion.

▲ **Fuel fires** : BIO FOR S is efficient on all hydrocarbon fires, such as diesel, kerosene, petrol... So it is perfectly usable for any vehicle fires.

▲ **Environment** : BIO FOR S is harmless for environment and totally biodegradable.

BIO FOR S is totally fluorine-free.

PHYSICAL DATA

Appearance	red liquid
Specific gravity at 20°C	1.01 ± 0.02 Kg/dm ³
pH at 20°C	7.0 ± 1.0
Viscosity at 20°C	4 ± 2 cStokes
Sediments	0 %
Surface tension at 1 %	25 ± 2 mN/m
Freezing point	- 5°C
Temperature of use	0°C / + 50°C

FOAM QUALITY AT 3 %

Low Expansion	> 8*
Drainage time 25 %	> 4 minutes
Medium Expansion	> 50*
High Expansion	> 700*

* Foam expansion values depend on the equipment



PERFORMANCES & APPLICATIONS

BIO FOR S can be used for all structural fires with tap water, sea water and brackish water. Depending on the fuel and the intervention – extinction or protection – we recommend different methods of application :

FIRES	APPLICATION	CONCENTRATION
Low fires: bush, grass, sawdust, tundra, muskeg...	Wetting	0.5 %
High fires : standing timber, structures, farms...	Wetting foaming LE*	1.0 %
Urban fires : flat, houses, warehouses	Foaming LE*	1.0 %
Vehicles fires : cars, tractors...	Foaming LE* / ME*	3.0 %
Solid fires : plastic, tyres, wood, cotton...	Wetting foaming LE*	1.0 %
Warehouse flooding	Foaming HE*	3.0 %
Hydrocarbon fires	Foaming LE*	3.0 %

* LE : Low Expansion * ME : Medium Expansion * HE : High Expansion

WARRANTY & SERVICES

BIO FOR S has a 10 years warranty in its original packaging and at storage temperatures -30°C/+60°C.

Our Quality Control Laboratory offers its analytical expertise BIO-LAB.

Safety Data and Environment Data are available upon request : contact@bio-ex.fr